

^ DIP SOLDERING MACHINE SERIES

PME-03VB

Twin-bowl automatic dip soldering machine

Twin vibration bowls

Feeds, flux dips, dip solders and unloads coils and relays fully automatically. Twin vibration bowls let two different products be loaded and soldered at the same time.



4-6 kg/cm²

AIR PRESSURE

920 × 700 mm

FOOTPRINT, L × W

900 × 400 mm

BOWL TABLE, L × W

KEY FEATURES

^ Coils and relays

Solders vertical or horizontal coil and relay components.

^ Twin vibration bowls

Two bowls let two different products be loaded and soldered at the same time.

^ Custom designs

Can be custom designed to a customer's special soldering requests and specifications.

^ Fully automatic process

Feeding, flux dipping, dip soldering and unloading are all automatic.

^ Programmable dip angle

The rotation angle for dip soldering is programmable.

^ Stable, labor saving

Stable, efficient and simple to operate, with lower labor costs.

SPECIFICATIONS

MODEL PME-03VB	
Operation	Touch panel interface
Control	Servo motor and PLC
Air pressure	4–6 kg/cm ²
Power	AC 220 V, 50/60 Hz
Dimensions	L920 × W700 × H1,300 mm
Vibration bowl table size	L900 × W400 × H1,100 mm

Specifications and design are subject to change without notice.

TYPICAL PRODUCTS

